

eneloop


Ready to use Rechargeable Battery™

CHARGE up to **2100** times CYCLES


Pre-Charged by Solar Energy
Ready to use



after 10 years
70%*
Capacity Remains




Why choose eneloop?



1 eneloop = **2100** pcs of disposable batteries

1) Battery tested at 20°C ambient temperature self-discharge condition 0.2It (E.V.=1.0V).

Size	Model No.	Capacity	Pc/Pack	Inner/Outer Qty
Eneloop Battery				
AA	BK-3MCCE/2BA	2000mAh	2	10pks / 60pks
AA	BK-3MCCE/4BA	2000mAh	4	10pks / 60pks
AAA	BK-4MCCE/2BA	800mAh	2	10pks / 60pks
AAA	BK-4MCCE/4BA	800mAh	4	10pks / 60pks

SEE OVER FOR CHARGERS



Log in to MI Link for more information, stock levels and easy online ordering for account holders.



Master Instruments Pty Ltd

Sydney: (02) 9519 1200

Perth: (08) 9302 5444

Web: www.master-instruments.com.au

Melbourne: (03) 9872 6422

Brisbane: (07) 3038 3250

Email: sales@master-instruments.com.au



062021

eneloop pro™



Pre-Charged by Solar Energy
Ready to use

after 1 year
85%*1
Capacity Remains



Size	Model No.	Capacity	Pc/Pack	Inner/Outer Qty
Eneloop Pro Battery				
AA	BK-3HCCE/4BT	2550mAh	4	10pks / 40pks
AA	BK-3HCCE/8BT	2550mAh	8	10pks / 40pks
AAA	BK-4HCCE/4BT	950mAh	4	10pks / 40pks

CHARGERS WITH BATTERIES



Smart & Quick Charger | K-KJ55MCC4TA

- World voltage auto detect 100-240VAC input via wall mount plug.
- LED Capacity & Battery Life Checker.
- Safety timer, peak voltage control, temperature control/protection.
- Individual management/-ΔV Control.
- Alkaline battery detection.
- Short circuited cells detection.
- Includes 4 x BK-3MCCE (AA) cells.



Basic Charger | K-KJ51MCC4TA

- World voltage auto detect 100-240VAC input via wall mount plug.
- 2 x LED indicators.
- Built in safety timer control (13 hours).
- Includes 4 x BK-3MCCE (AA) cells.

Specifications

Input	AC100-240V 50-60Hz
Output	DC1.5 V AA 550mA x4 / AAA 275mA x4
Indicator	LED x 4 Charging: ON, Fully charged: OFF
Suitable for	AA x 1, 2, 3, 4 / AAA x 1, 2, 3, 4 cells
Charging time	AA: ~1.5hours (1-2pc) / ~3hours (3-4pc) [2,000mAh] AAA: ~1.5hours (1-2pc) / ~3hours (3-4pc) [800mAh]
Charger size / Weight	68 x 120 x 75 cm (W x H x D) / 120g

Specifications

Input	AC100-240V 50-60Hz
Output	DC 3V AA 250mA x 2 / AAA 120mA x 2
Indicator	LED x 4 Charging: ON, Fully charged: OFF
Suitable for	AA x 2, 4 / AAA x 2, 4 cells
Charging time	AA: ~10hours (2pc / 4pc) [2,000mAh] AAA: ~10hours (2pc / 4pc) [800mAh]
Charger size / Weight	66 x 108 x 70 cm (W x H x D) / 96g

1) Battery tested at 20°C ambient temperature self-discharge condition 0.2It (E.V.=1.0V).